# **2K MOUNT SERIES**

Two stage shock mount and vibration isolator for severe dynamic environments such as shipboard and ground vehicles.

#### APPLICATIONS

- Naval sonar equipment
- Shipboard electronics
- Radar installations
- Computer & video displays

#### FEATURES

- Combines shock and vibration isolation in a single isolator
- Protects from vibratory inputs as low as 10 Hz
- Designed for base mounting only
- Wide load range for most applications

#### BENEFITS

- Elastomeric shock attenuating elements have as much as 1 inch of available deflection (1.5 inches for 2KS)
- Limit shock transmissions to 20g's when subjected to a five foot hammer blow per MIL-S-901
- Many custom versions are available. Consult factory for more information

## LOAD RANGE

- 2K1 Series = 4 load ratings from 1 - 10 lbs. per mount
- 2K2 Series = 8 load ratings from 4 - 90 lbs. per mount
- 2KS Series for loads from 250 -6,000 lbs.



Barry 2K-Series mounts offer the advantage of superior vibration and shock protection for a wide range of loads in a single compact unit. These isolators are ideal for isolating naval sonar equipment, shipboard electronics and communications.

## **Specifications**

<ul> <li>Natural Frequency</li> <li>Vibration Element</li> </ul>	6-8 Hertz vertical
Shock Element	15 Hertz
• Transmissibility at resonance	
Vibration Element	2.5 Max.
Shock Element	10 Max.
Resilient Element	
Vibration Element	Friction Damped Spring
Shock Element	Neoprene or Nitrile Elastomer
Standard Materials	Varies with model
	(Standard Beryllium Copper Restraining
	Strap)
Weight	See dimensional drawings

# **Environmental Data**

- 2K1 and 2K2 isolators are for use with lightweight MIL-S-901 applications.
- 2KS systems are for use with medium weight MIL-S-901 applications.
- Isolators and systems met MIL-STD-16400 inclination, temperature, humidity and salt spray specifications, MIL-STD-167 vibration tests and MIL-M-17185 environmental and oil immersion tests.
- Operating temperature range is -20°F to +180°F (-30°C to +82°C).
- Isolators are unaffected by humidity, sand, dust and fungus.